

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 1 249 214 A2**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
16.10.2002 Bulletin 2002/42

(51) Int Cl.7: **A61F 13/496**

(21) Application number: **02252548.9**

(22) Date of filing: **10.04.2002**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR**
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• Otsubo, Toshifumi, c/o Technical Center
Mitoyo-gun, Kagawa-ken, 769-1602 (JP)
• Yamamoto, Hiroki, c/o Technical Center
Mitoyo-gun, Kagawa-ken, 769-1602 (JP)

(30) Priority: **12.04.2001 JP 2001114563**

(74) Representative: **Parry, Christopher Stephen
Saunders & Dolleymore,
9 Rickmansworth Road
Watford, Herts. WD18 0JU (GB)**


(71) Applicant: **UNI-CHARM CORPORATION
Kawanoe-shi Ehime-ken (JP)**

(54) **Disposable pants-type diaper**

(57) A disposable pants-type diaper 1 includes a front waist region sheet 2, a rear waist region sheet 3 and a body fluid absorbent pad 4. The front and rear waist region sheets 2, 3 are bonded together in the vicinity of transversely opposite side edges 16, 17 thereof and the pad 4 is curved in a U-shape and has longitudinally opposite ends 36, 37 bonded to the inner side of the front and rear waist region sheets 2, 3. Periphery of

a lower edge 13 of the front waist region sheet 2 draws a curve which is convex upward and this lower edge 13 intersects transversely opposite side edges 35a of the pad 4 to define tops 42 of a pair of leg-holes 41. A first elastic member 23 extending along the lower edge 13 of the front waist region sheet 2 intersects third elastic members 39 of the pad 4 in the vicinity of the tops 42 and then descend rearward of the diaper 1.

FIG.3



EP 1 249 214 A2

BEST AVAILABLE COPY

Description

[0001] This invention relates to a disposable pants-type diaper for absorption and containment of body wastes.

[0002] Japanese Patent Application No. 1987-243806A discloses a disposable pants-type diaper composed of a front waist region, a rear waist region and a crotch region extending between these two waist regions. As viewed in its flatly developed state, semi-elliptic cutouts destined to define respective leg-holes are shaped so as to be put aside toward the front waist region with respect to a center line X bisecting a longitudinal length of the diaper. The diaper developed in this manner is folded back along the center line X to be placed one half upon another half and transversely opposite side edges are put flat and bonded together to obtain the pants-type diaper. In the pants-type diaper obtained in this manner, tops of the respective leg-holes lie in the front waist region. In this diaper, elastic members horizontally extending in a transverse direction of the diaper cooperate with elastic members vertically extending in a longitudinal direction of the diaper to surround the respective leg-holes. The tops of the respective leg-holes come substantially in coincidence with thigh tops of a baby wearing this diaper as the baby sits on the floor, so there is no anxiety that the tops of the respective leg-holes might uncomfortably compress the thigh tops of the baby.

[0003] Japanese Patent Application No. 1991-139349A also discloses a disposable pants-type diaper composed of a front waist region, a rear waist region and a crotch region extending between these two waist regions. In this diaper, elastic members provided in the front waist region so as to extend downward from a top of the front waist region drawing a circular arc, elastic members provided in the rear waist region so as to extend downward from a top of the rear waist region drawing a circular arc and elastic members provided in the crotch region so as to extend in back-and-forth direction cooperate together to surround respective thighs of the wearer.

[0004] Also in the case of the diaper disclosed in the above-cited Publication No. 1987-243806A, there is no serious anxiety that the tops of the respective leg-holes might uncomfortably compress the thigh tops of a baby wearing this diaper as the baby sits on the floor. However, the elastic members extend in no parallel to the leg-holes and may sometimes compress the tops of the respective thighs.

[0005] Fig. 10 of the accompanying drawings is a fragmentary side view illustrating a baby wearing the diaper 201 disclosed in the Publication No. 1991-139349A and sitting on the floor. With this diaper 201, both the tops 242 of the leg-holes and the elastic members 223, 224 extending along these tops 242 lie on transversely opposite side edges of the diaper 201 not in coincidence with the tops of the thighs. In consequence, these elastic

members 223, 224 may compress the tops of baby's thighs and slide down as indicated by imaginary lines.

[0006] It is an object of this invention to improve the diaper well known from the disclosures of above-cited Publication so that elastic members associated with leg-holes might neither compress tops of baby's thighs nor slide down as the baby sits on the floor.

[0007] According to this invention, there is provided a disposable pants-type diaper comprising a front waist region sheet contoured by a first upper edge extending in a horizontal direction or a transverse direction of the diaper, a pair of first side edges intersecting the first upper edge and extending in parallel to and spaced from each other and intersecting the first upper edge and a first lower edge opposed to the first upper edge delineating a curve convex upward in a longitudinal direction of the diaper, a rear waist region sheet contoured by a second upper edge and a pair of second side edges extending in parallel to the first upper edge and first side edges, respectively, and a second lower edge opposed to the second edge delineating a curve convex downward in the longitudinal direction and a body fluid absorbent pad having inner and outer surfaces, wherein the front waist region sheet is bonded to the rear waist region sheet in the vicinity of the first and second side edges, the body fluid absorbent pad extending with an inner surface inside upward with its opposite ends curved in a U-shape and with an inner surface inside has its outer surface bonded to respective inner surfaces of the front and rear waist region sheets, the first and second upper edges of the front and rear waist region sheets define a waist-hole, the first and second lower edges of the front and rear waist region sheets together with the side edges of the pad define a pair of leg-holes, and elastic members extending in parallel to peripheral edges of these waist-hole and leg-holes impart an elastically stretchable property to the respective peripheral edges of these holes.

[0008] The pair of leg-holes has further respective tops as viewed in the vertical direction or the longitudinal direction of the diaper, the tops being defined by the first lower edge of the front waist region sheet and the side edges of the pad. The elastic members extending in parallel to the respective peripheral edges of the leg-holes comprise a first elastic member attached to the front waist region sheet in parallel to its first lower edge, a second elastic member attached to the rear waist region sheet in parallel to its second lower edge and third elastic members attached to the pad in parallel to its side edges. The first elastic member attached to the front waist region descends rearward of the diaper from the tops to the vicinity of the first side edges; the second elastic member descends from the vicinity of the second side edges rearward of the diaper. The first and second elastic members are substantially contiguous to each other in the vicinity of intersections of the first and second side edges; and the third elastic member intersects the first elastic member in the vicinity of the tops, and

intersects the second elastic member at a position lower than the second side edges.

Fig. 1 is a partially cut away perspective view of the disposable pants-type diaper as viewed from the front side;

Fig. 2 is a perspective view of the diaper shown in Fig. 1 as viewed from the rear;

Fig. 3 is a front view of the diaper shown in Fig. 1;

Fig. 4 is a rear view of the diaper shown in Fig. 1;

Fig. 5 is a side view illustrating the diaper worn by a baby sitting on the floor;

Fig. 6 is a diagram schematically illustrating a process for making the diaper shown in Fig. 1;

Fig. 7 is a cross-sectional view of the pad shown in Fig. 6 as taken along a line VII - VII in Fig. 6;

Fig. 8 is a cross-sectional view similar to Fig. 7 but showing another embodiment of the pad;

Fig. 9 is a diagram similar to Fig. 6 but illustrating another embodiment of the process for making the diaper; and

Fig. 10 is a side view illustrating the conventional pants-type diaper worn by a baby sitting on the floor.

[0009] Details of a disposable pants-type diaper according to this invention will be more fully understood from the description given hereunder in reference to the accompanying drawings.

[0010] Fig. 1 is a partially cut away perspective view showing a disposable pants-type diaper 1 as viewed from its front side and Fig. 2 is a perspective view of the diaper 1 as viewed from its rear side. The diaper 1 comprises a front waist region sheet 2 lying on a front side of a wearer's waist, a rear waist region sheet 3 lying on a rear side of the wearer's waist and a body fluid absorbent pad 4 curved in a U-shape and lying in a crotch region. The front and rear waist region sheets 2, 3 are formed of a sheet material such as a nonwoven fabric, plastic film or laminated sheet consisting of these nonwoven fabric and film. A lateral width of each of these sheets 2, 3 is greater than half the circumferential dimension of the diaper 1 and transversely opposite side edges of these sheet 2,3 are overlaid and joined together at a plurality of zones 6 arranged intermittently in a longitudinal direction of the diaper 1 so as to form an annular waist region 5 and an annular waist-hole 7. The front and rear waist region sheets 2, 3 respectively have upper edges 11, 12 and lower edges 13, 14 extending in a transverse direction of the diaper 1, and pairs of side edges 16, 17 extending in parallel to each other in longitudinal direction of the diaper 1. These sheets 2, 3 are respectively provided on inner surfaces thereof with upper stretchable elastic members 18, 19, each comprising a plurality of elastic threads, extending in parallel to the upper edges 11, 12 and secured under extension thereto. These stretchable elastic members 18, 19 allow a peripheral edge of the waist-hole 7 to be placed against the wearer's waist with a uniform fitness. The

front and rear waist region sheets 2, 3 are further provided on the inner surfaces thereof with lower stretchable elastic members 23, 24, each comprising a plurality of elastic threads, extending in parallel to the lower edges 13, 14 and secured under extension thereto.

[0011] The pad 4 comprises a liquid-pervious top-sheet 31 facing the wearer's skin, a backsheet 32 facing the wearer's clothes and a body fluid absorbent core 33 interposed between these two sheets 31, 32. The top- and backsheets 31, 32 extend outward by beyond a peripheral edge of the core 33 and are overlaid and bonded together over respective extended zones so as to form a pair of flaps 35 outside the peripheral edge of the core 33. The pad 4 curved in a U-shape has front and rear upper ends 36, 37 of which the upper end 36 is bonded to an inner surface of the front waist region sheet 2 and the upper end 37 is joined to the inner surface of the rear waist region sheet 3. The flaps 35 are respectively provided along transversely opposite side edges 35a thereof with stretchable elastic members 39, each comprising a single elastic thread or a plurality of elastic threads, extending upwardly in a U-shape and bonded under extension to the inner surface of at least one of the top- and backsheets 31, 32. The side edges 35a of the respective flaps 35 corresponding to the side edges of the pad 4 intersect the respective lower edges 13, 14 of the front and rear waist region sheets 2, 3 so as to form leg-holes 41. The stretchable elastic members 39 associated with the side edges of the pad 4 cooperate with the respective lower stretchable elastic members 23, 24 of the front and rear waist region sheets 2, 3 to form stretchable elastic members associated with the respective leg-holes of the diaper 1.

[0012] Fig. 3 is a front view of the diaper 1. Periphery of the lower edge 13 of the front waist region sheet 2 draws a curved line which is convex upward. Intersections of this lower edge 13 with the respective side edges 35a of the pad 4 define respective tops 42 of the leg-holes 41 as viewed in a vertical direction. The lower stretchable elastic members 23 extend horizontally between the respective tops 42 of the leg-holes 41 and descend from the respective tops 42 rearward to the vicinity of the side edges 16. Such lower stretchable elastic members 23 intersect with the stretchable elastic members 39 extending along the side edges of the pad 4 in the vicinity of the respective tops 42.

[0013] Fig. 4 is a rear view of the diaper 1. Periphery the lower edge 14 of the rear waist region sheet 3 draws a curved line which is convex downward. The lower elastic members 24 extend downward along the lower edge 14 of the rear waist region sheet 3 from the vicinity of the side edges 17 rearward and then extend horizontally across the pad 4. Such lower elastic members 24 intersect the elastic members 39 extending along the side edges of the pad 4 at a position lower than the side edges 17. Referring to Figs. 3 and 4, the lower elastic members 23, 24 extending across the pad 4 function to bring the pad 4 in close contact with the wearer's body.

If such function is not desired, it is possible to cut off the respective lower elastic members 23, 24 in the ranges A, B defined between the intersections of the lower elastic members 23, 24 with the elastic members 39 extending along the side edges of the pad 4.

[0014] Fig. 5 is a fragmentary side view illustrating a baby 43 wearing the diaper 1 and sitting on the floor. As seen in Fig. 5, the tops 42 of the leg-holes 41 substantially coincide with respective tops 44 of the thighs 45b of the baby 43 and the lower elastic members 23, 24 of the front and rear waist region sheets 2, 3 are substantially contiguous to each other in the vicinity of the zones 6 in which the first side edges 16 and the second side edges 17 are bonded together. Consequently, the lower elastic members 23, 24 descend rearward from the tops 42 to a hip 45a of the baby 43, drawing substantially straight lines or gently curved lines. With the diaper 1 worn in this manner, stretch and contraction of the lower elastic members 23, 24 due to a movement of the thighs 45 and the hip 45a of the baby 43 occurring as the baby 43 sits on the floor as illustrated merely intensifies or weakens a tightening effect around the thighs 45 rather than causing the diaper 1 to slide down along the thighs 45 as has been the case with the diaper of well known art. In this way, position of the diaper 1 is stabilized around the thighs 45.

[0015] Fig. 6 is a diagram schematically illustrating important part of a process for making the diaper 1, in which a machine direction is indicated by an arrow md and a direction orthogonal to the machine direction is indicated by an arrow cd. The process comprises first - eight steps 51 - 58. In the first step 51, a single web 61 is continuously fed from the left side of the drawing in Fig. 6 to the machine direction md.

[0016] In the second step 52, the elastic members 64, 66 associated with the waist-hole, each comprising a plurality of elastic threads 62, 63, are continuously fed onto the respective side edges of the web 61 and attached to an upper surface of the web 61 by means of an adhesive (not shown). The adhesive may be applied to the elastic threads 62, 63 or on the web 61.

[0017] In the third step 53, a first elastic member 73 associated with one leg-hole comprising a plurality of elastic threads 67, and a second elastic member 74 associated with the other leg-hole comprising a plurality of elastic threads 68, are continuously fed under a desired extension onto the upper surface of the web 61 so as to draw substantially sinusoidal curves and attached thereto by means of an adhesive (not shown). In this way, a composite web 65 comprising the web 61 and the respective elastic members 64, 66, 73, 74 are obtained. The first elastic member 73 associated with the one leg-hole and the second elastic member 74 associated with the other leg-hole are symmetric about a center line c of the web 61 and shifted to the md direction by a length corresponding to half cycle a. More specifically, if the first elastic member 73 associated with one leg-hole is shifted in the machine direction md by the

half cycle a from the state illustrated in Fig. 6, profile of a curve defined by a trough 76 and a crest 77 drawn by the first elastic member 73 associated with the one leg-hole will be symmetric to the corresponding profile of the curve defined by a crest 78 and a trough 79 drawn by the second elastic member 74 associated with the other leg-hole about the center line c.

[0018] In the fourth step 54, the web 61 is cut into a first half web 81 and a second half web 82 along a line d bisecting a width of the distance between the first elastic member 73 associated with the one leg-hole and the second elastic member 74 associated with the other leg-hole, and these two half webs 81, 82 are displaced in parallel to the direction cd orthogonal to the machine direction md to space these two half webs 81, 82 from each other by a desired dimension D1.

[0019] In the fifth step 55, individual body fluid absorbent pads 84, each of which is illustrated as partially cut away, are placed upon the first and second half webs 81, 82 so that the pads 84 may overlap these half webs 81, 82 and thereby connect them to each other. In the overlapping zones, the pads 84 are bonded to the respective half webs 81, 82 by means of an adhesive (not shown) to obtain a first continuum 85 of diapers. A dimension of the pad 84 in the machine direction md is shorter than the length corresponding to the half cycle a and one pad 84a of two pads 84 which are adjacent to each other in the machine direction md lies so as to be in the center of the trough 76 drawn by the first elastic member 73 associated with the one leg-hole and the trough 79 drawn by the second elastic member 74 associated with the other leg-hole. The other pad 84b lies so as to be in the center of the crest 77 drawn by the first elastic member 73 associated with the one leg-hole and the crest 78 drawn by the second elastic member 74 associated with the other leg-hole. In these adjacent pads 84a, 84b, a distance 86 from the one web side edge 46 to the pad 84a is equal to a distance D2 from the other web side edge 47 to the pad 84b. While the pads 84 really have the body fluid absorbent cores 33 and the elastic members 39 extending along the respective side edges thereof (See Fig. 7), Fig. 6 illustrates only an external shape of these pads 82 placed on the web 61. The first and second half webs 81, 82 and the first and second elastic members 73, 74 associated with the respective leg-holes underlying the pads 84 are indicated by imaginary lines to clarify the presence of these half webs 81, 82 and the elastic members 73, 74.

[0020] In the sixth step 56, the first continuum 85 of diapers is folded back onto itself along a center line e extending in the machine direction md and bisecting a dimension of this continuum 85 in the direction orthogonal to the machine direction md with the pads 84 inside to a second continuum 88 of diapers.

[0021] In the seventh step 57, the first and second half webs 81, 82 placed upon each other to form the second continuum 88 of diapers are bonded together in zones 89 extending along lines f each bisecting a distance be-

tween each pair of the adjacent pads 84, 84.

[0022] In the eighth step 58, the second continuum 88 of diapers is cut along lines indicated by arrows 90, i.e., along the lines f so as to bisect the respective zones 89 to right and left halves and thereby individual diapers 101 are obtained. As will be apparent from the diagram, each diapers 101 are obtained for every half cycle a of the substantially sinusoidal curves drawn by the first and second elastic members 73, 74 associated with the respective leg-holes. The diapers 101 having the pads 84a and showing their front-sides and the diapers 101 having the pads 84b and showing their rear-sides are alternately obtained as the second continuum 88 of diapers is cut along the lines f. Whether the diapers 101 show front-sides or rear-sides in the final step of the process for making the diaper, these individual diapers 101 are identical one to another. Specifically, these individual diapers 101 are identical one to another in that the elastic members 64, 66 associated with the waist-hole are placed upon each other and the first and second elastic members 73, 74 associated with the respective leg-holes are placed upon each other in the bonding zones 89.

[0023] Each of the diapers 101 obtained by the process described above corresponds to the diaper 1 shown in Fig. 1 and each of the pads 84 of the diapers 101 corresponds to the pad 4 of the diaper 1. In the case of the diapers 101 having the pad 84a, the first and second half webs 81, 82 respectively define the rear waist region sheet 3 and the front waist region sheet 2 of the diaper 1. The elastic members 64, 66 associated with the waist-hole respectively define the upper elastic members 19, 18 of the rear waist region sheet 3 and the front waist region sheet 2 in the diaper 1. The first and second elastic members 73, 74 respectively define the lower elastic members 24, 23 of the front waist region sheet 2 and the rear waist region sheet 3 in the diaper 1. In the case of the diapers 101 having the pad 84b, the first and second half webs 81, 82 respectively define the front waist region sheet 2 and the rear waist region sheet 3 of the diaper 1. The elastic members 64, 66 associated with the waist-hole respectively define the upper elastic members 18, 19 of the rear waist region sheet 3 and the front waist region sheet 2 in the diaper 1. The first and second elastic members 73, 74 respectively define the lower elastic members 23, 24 of the front waist region sheet 2 and the rear waist region sheet 3 in the diaper 1. In the case of the diapers 101 having the pad 84a, the respective tops 42 of the leg-holes 41 in the diaper 1 are defined by the intersections of the second half web 82 and the pad 84a. In the case of the diaper 101 having the pad 84b, on the other hand, the respective tops 42 of the leg-holes 41 in the diaper 1 are defined by the intersections (not shown) of the first half web 81 and the pad 84b.

[0024] A stock material for the web 61 used in this process may be selected from a group of materials including a nonwoven fabric, a plastic film and a compos-

ite sheet consisting of these nonwoven fabric and plastic film. The web 61 may be liquid-impervious or breathable and liquid-impervious or liquid-pervious. The first and second elastic members 73, 74 drawing substantially sinusoidal curves have the respective crests 77, 78 and the troughs 76, 79 which may be rectilinear in parallel to the center line c of the web 61 as illustrated or curvilinear. The number of the elastic threads 67, 68 respectively forming the first and second elastic members 73, 74 associated with the leg-holes may be appropriately increased or reduced.

[0025] Fig. 7 is a cross-sectional view of the pad 84 as taken along a line VII - VII in Fig. 6. The pad 84 is the same as the pad 4 shown in Fig. 1, i.e., comprises the liquid-pervious topsheet 31, the liquid-impervious backsheet 32 and the body fluid absorbent core 33 interposed between these two sheets 31, 32. In the flaps 35 extending outside the side edges of the core 33, the elastic members 39 extend along the side edges of these flaps 35 and disposed between the top- and back-sheets 31, 32. The topsheet 31 may be formed of a nonwoven fabric or an apertured plastic film and the backsheet 32 may be formed of a plastic film.

[0026] Fig. 8 is a view similar to Fig. 7 but showing a pad 87 according to another embodiment replacing the pad 84 shown in Fig. 7. In the case of this pad 87, portion of the backsheet 32 extending outwardly beyond the topsheet 31 in the flaps 35 is folded back onto inner side of the pad 87. The elastic members 39 extending along the side edges of the flaps 35 lie slightly inside above the pad 35. In the case of this pad 87, folded regions 87 of the respective flaps 35 partially form the respective leg-holes. While external shapes of all the illustrated pads 4, 84, 87 are rectangular, shapes of these pads may be hourglass-shaped, in which the side edges 35a are curved inward in middle zones to rear and front directions thereof. In this case, the elastic members 39 may extend in the rear and front directions along the curved side edges 35a.

[0027] Fig. 9 is a view similar to Fig. 6 but illustrating a part of the process of another embodiment for making the diapers 101. In the third step 53 of this alternative process, the first and second elastic members 73, 74 each comprising a plurality of elastic threads under extension are fed onto the regions of the web corresponding to the first and second half webs 81, 82 in the fourth step 54 so that these elastic members 73, 74 may be distributed uniformly as much as possible over the direction cd. While the respective components of the diapers 101 obtained in this manner are designated by reference numerals similar to those in the diaper 1 shown in Fig. 1, both the front waist region sheet 2 and the rear waist region sheet 3 are stretchable and contractible in the transverse direction of the diaper 1. On the front waist region sheet 2, the elastic member 73 or 74 associated with the leg-hole lying in the vicinity of each of the leg-holes 41 descends from the top 42 of each of the leg-holes 41 toward the bonding zones 6 and, on the

rear waist region sheet 3, the elastic member 73, 74 lying in the vicinity of the leg-hole 41 extends along the leg-hole 41 and descends from the bonding zones 6 toward the pad 4. In such diapers 101 also, the elastic member 73 or 74 extending along the peripheral edge one of the leg-holes 41 extends rearward from the top 42 drawing a substantially straight line, so there is no anxiety that the elastic members 73, 74 associated with the leg-holes 41 might slide down along the thighs 45 even if the baby wearing the diapers 101 sits on the floor as illustrated in Fig. 5.

[0028] While the front and rear waist region sheets 2, 3 of the diaper 1, 101 are respectively formed by a single layered sheet material in the embodiments as illustrated and described, these sheets 2, 3 may be respectively formed by a laminated sheet material each comprising two layers of a sheet material. In such case, the upper elastic members 18, 19 and the lower elastic members 23, 24 are preferably interposed between these two layers of sheet material and bonded to the inner surface of one of these two layers of a sheet material. In the diaper 1 shown in Figs. 1 and 2, not only the longitudinally opposite ends 36, 37 of the pad 4 but also the zones of the pad 4 in which the elastic members 39 intersect the lower elastic members 23, 24 may be bonded to the front and rear waist region sheets 2, 3 to improve fitness of the diaper 1 to the wearer around the wearer's thighs.

[0029] The disposable pants-type diaper according to this invention is characterized in that the tops of the leg-holes lie in the front waist region and the elastic members associated with the leg-holes descend from the respective tops thereof rearward drawing substantially straight lines. Such unique arrangement is effective to avoid the anxiety that the elastic members associated with the leg-holes might slide down along the thighs even if the baby wearing this diaper sits on the floor.

Claims

1. A disposable pants-type diaper comprising a front waist region sheet contoured by a first upper edge extending in a horizontal direction or a transverse direction, a pair of first side edges intersecting said upper edge and extending in parallel to and spaced from each other and a first lower edge opposed to said first upper edge delineating a curve convex upward in a longitudinal direction of said diaper, a rear waist region sheet contoured by a second upper edge and a pair of second side edges extending in parallel to said first upper edge and first side edges, respectively, and a second lower edge opposed to said second edge delineating a curve convex downward in said longitudinal direction and a body fluid absorbent pad having inner and outer surfaces, said front waist region sheet being bonded to said rear waist region sheet in the vicinity of said first and second side edges, said body fluid absorbent pad

extending upward with its opposite ends curved in a U-shape with said inner surface inside where to opposite ends of said pad have said outer surface bonded to respective inner surfaces of said front and rear waist region sheets, said first and second upper edges of said front and rear waist region sheets define a waist-hole, said first and second lower edges of said front and rear waist region sheets together with said side edges of said pad define a pair of leg-holes, and elastic members extending in parallel to peripheral edges of said waist-hole and leg-holes impart an elastically stretchable property to said respective peripheral edges of said holes,

said disposable pants-type diaper further comprising:

said pair of leg-holes having respective tops as viewed in said vertical direction or the longitudinal direction of said diaper, said tops being defined by said first lower edge of said front waist region sheet and said side edges of said pad;

said elastic members which extend in parallel to the respective peripheral edges of said leg-holes including a first elastic member attached to said front waist region sheet in parallel to its first lower edge, a second elastic member attached to said rear waist region sheet in parallel to its second lower edge and third elastic members attached to said pad in parallel to its side edges;

said first elastic member attached to said front waist region descending rearward of said diaper from said tops to the vicinity of said first side edges;

said second elastic member descending from the vicinity of said second side edges rearward of said diaper;

said first and second elastic members being substantially contiguous to each other in the vicinity of intersections of said first and second side edges; and

said third elastic member intersecting said first elastic member in the vicinity of said tops, and intersecting said second elastic member at a position lower than said second side edges.

2. The diaper according to Claim 1, wherein said first elastic member attached to said front waist region sheet extends from one of said tops to the other of said tops in parallel to said first lower edge across said pad.
3. The diaper according to Claim 1, wherein said first elastic member attached to said front waist region sheet extends between said tops and the vicinity of said first side edges and is cut off between said

tops.

4. The diaper according to Claim 1, wherein said second elastic member attached to said rear waist region sheet extends in parallel to said second lower edge from one of said second side edges across said pad to the other of said second side edges. 5
5. The diaper according to Claim 1, wherein said second elastic member attached to said rear waist region sheet is cut off between intersections of said second elastic member and said third elastic member. 10
6. The diaper according to Claim 1, wherein said first and second elastic members extend substantially straight in parallel to the peripheral edges of said leg-holes. 15

20

25

30

35

40

45

50

55

FIG.1




FIG.2




FIG.3




FIG.4




FIG.5




FIG.6




FIG.7




FIG.8




FIG.9






FIG.10





(19)

Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 249 214 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
12.05.2004 Bulletin 2004/20

(51) Int Cl.7: A61F 13/496, A61F 13/15

(43) Date of publication A2:
16.10.2002 Bulletin 2002/42

(21) Application number: 02252548.9

(22) Date of filing: 10.04.2002

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• Otsubo, Toshifumi, c/o Technical Center
Mitoyo-gun, Kagawa-ken, 769-1602 (JP)
• Yamamoto, Hiroki, c/o Technical Center
Mitoyo-gun, Kagawa-ken, 769-1602 (JP)

(30) Priority: 12.04.2001 JP 2001114563

(74) Representative: Parry, Christopher Stephen
Saunders & Dolleymore,
9 Rickmansworth Road
Watford, Herts. WD18 0JU (GB)


(71) Applicant: UNI-CHARM CORPORATION
Kawanoe-shi Ehime-ken (JP)

(54) Disposable pants-type diaper

(57) A disposable pants-type diaper 1 includes a front waist region sheet 2, a rear waist region sheet 3 and a body fluid absorbent pad 4. The front and rear waist region sheets 2, 3 are bonded together in the vicinity of transversely opposite side edges 16, 17 thereof and the pad 4 is curved in a U-shape and has longitudinally opposite ends 36, 37 bonded to the inner side of the front and rear waist region sheets 2, 3. Periphery of

a lower edge 13 of the front waist region sheet 2 draws a curve which is convex upward and this lower edge 13 intersects transversely opposite side edges 35a of the pad 4 to define tops 42 of a pair of leg-holes 41. A first elastic member 23 extending along the lower edge 13 of the front waist region sheet 2 intersects third elastic members 39 of the pad 4 in the vicinity of the tops 42 and then descend rearward of the diaper 1.

FIG.3



EP 1 249 214 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 02 25 2548

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
E	EP 1 240 881 A (UNI CHARM CORP) 18 September 2002 (2002-09-18) * column 4, line 10 - column 8, line 45; figures 1-6 *	1-6	A61F13/496 A61F13/15
A	US 5 836 932 A (BUELL KENNETH BARCLAY ET AL) 17 November 1998 (1998-11-17) * column 5, line 13 - column 7, line 65; figure 1 *	1-6	
A,D	JP 62 243806 A (UNI CHARM CORP) 24 October 1987 (1987-10-24) * the whole document; figures *	1-6	
A	EP 0 797 970 A (UNI CHARM CORP) 1 October 1997 (1997-10-01) * column 3, line 1 - line 38; figures 1-3 *	1-6	
A	EP 0 688 551 A (UNI CHARM CORP) 27 December 1995 (1995-12-27) * column 3, line 30 - column 5, line 57; figures *	1-6	TECHNICAL FIELDS SEARCHED (Int.Cl.7)
A	EP 0 832 628 A (KIMBERLY CLARK CO) 1 April 1998 (1998-04-01) * the whole document *	1-6	A61F
The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 17 March 2004	Examiner Boccignone, M
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 02 25 2548

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

17-03-2004

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 1240881	A	18-09-2002	JP 2002272781 A	24-09-2002
			AU 2323802 A	19-09-2002
			CA 2376419 A1	15-09-2002
			CN 1375269 A	23-10-2002
			EP 1240881 A2	18-09-2002
			TW 531410 B	11-05-2003
			US 2002129888 A1	19-09-2002
US 5836932	A	17-11-1998	US 5569234 A	29-10-1996
			US 6258077 B1	10-07-2001
			US 5769838 A	23-06-1998
			AT 213145 T	15-02-2002
			AU 721731 B2	13-07-2000
			AU 5325396 A	23-10-1996
			AU 5382996 A	23-10-1996
			BR 9604800 A	09-06-1998
			CA 2216145 A1	10-10-1996
			CA 2216640 A1	10-10-1996
			CA 2305868 A1	10-10-1996
			CA 2305876 A1	10-10-1996
			CA 2305879 A1	10-10-1996
			CN 1183714 A	03-06-1998
			CZ 9703126 A3	18-03-1998
			DE 69619279 D1	21-03-2002
			DE 69619279 T2	17-10-2002
			DE 69622028 D1	01-08-2002
			DE 69622028 T2	06-02-2003
			EG 21212 A	28-02-2001
			EP 0902674 A2	24-03-1999
			EP 0818980 A1	21-01-1998
			ES 2168469 T3	16-06-2002
			ES 2175085 T3	16-11-2002
			HU 9801605 A2	28-10-1998
			ID 25774 A	14-11-1996
			ID 24577 A	14-11-1996
			JP 2904934 B2	14-06-1999
			JP 10510335 T	06-10-1998
			JP 10505778 T	09-06-1998
			JP 2001353181 A	25-12-2001
			KR 266497 B1	15-09-2000
			KR 266498 B1	15-09-2000
			KR 263228 B1	01-09-2000
			KR 263229 B1	01-09-2000
			KR 272078 B1	15-11-2000
			NO 974541 A	03-12-1997
			TR 9701095 T1	21-03-1998

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

ANNEX TO THE EUROPEAN SEARCH REPORT ON EUROPEAN PATENT APPLICATION NO.

EP 02 25 2548

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

17-03-2004

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5836932	A		WO 9631178 A2	10-10-1996
			WO 9631179 A2	10-10-1996
			ZA 9602691 A	25-07-1996
JP 62243806	A	24-10-1987	JP 1909487 C	09-03-1995
			JP 6037722 B	18-05-1994
			DE 3781710 D1	22-10-1992
			EP 0241925 A1	21-10-1987
			ES 2034978 T3	16-04-1993
			GB 2189133 A ,B	21-10-1987
			KR 9501381 B1	18-02-1995
			US 4743241 A	10-05-1988
EP 0797970	A	01-10-1997	JP 3317836 B2	26-08-2002
			JP 9224973 A	02-09-1997
			CN 1174122 A ,B	25-02-1998
			EP 0797970 A2	01-10-1997
			ID 16259 A	18-09-1997
			SG 66355 A1	20-07-1999
			US 5858151 A	12-01-1999
EP 0688551	A	27-12-1995	JP 3186263 A	14-08-1991
			JP 7059243 B	28-06-1995
			EP 0688551 A2	27-12-1995
			AU 641454 B2	23-09-1993
			AU 6812590 A	20-06-1991
			CA 2032388 A1	19-06-1991
			DE 69027592 D1	01-08-1996
			DE 69027592 T2	06-02-1997
			DE 69032509 D1	27-08-1998
			DE 69032509 T2	22-04-1999
			EP 0437771 A2	24-07-1991
			GB 2239783 A ,B	17-07-1991
			GB 2266445 A ,B	03-11-1993
			KR 9601479 Y1	17-02-1996
			US 5334152 A	02-08-1994
			US 5645543 A	08-07-1997
			US 5055103 A	08-10-1991
			US 5197960 A	30-03-1993
EP 0832628	A	01-04-1998	EP 0838205 A2	29-04-1998
			EP 0832628 A2	01-04-1998
			AU 657994 B2	30-03-1995
			AU 2350692 A	18-03-1993
			BR 9203247 A	13-04-1993
			CA 2057739 A1	12-03-1993

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 02 25 2548

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

17-03-2004

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0832628 A		DE 69227563 D1	17-12-1998
		DE 69227563 T2	17-06-1999
		DE 69232745 D1	26-09-2002
		DE 69232745 T2	24-04-2003
		DE 69233301 D1	11-03-2004
		EG 19451 A	30-03-1995
		EP 0532034 A2	17-03-1993
		ES 2122977 T3	01-01-1999
		ES 2180869 T3	16-02-2003
		JP 3313418 B2	12-08-2002
		JP 5200069 A	10-08-1993
		KR 217833 B1	01-09-1999
		MX 9204691 A1	01-03-1993
		TR 27362 A	17-01-1995
		US 5685873 A	11-11-1997
		ZA 9206773 A	10-03-1993

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

THIS PAGE BLANK (USPTO)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)